

RHG 3AC

RHG

漩涡式气泵在真空和压力操作的选型和订购参数。

订单型号	马达				重量	噪音	最大流量	最大真空	最高压力	真空阀
	额定									
	有库存	输出功率	电压	电流						
	HZ	KW	V	A	KG	db(A)	m³/h	mbar	mbar	类型*型号
RHG 510-7H1	50	0.85	200-240 ^Δ /345-415	4.0 ^Δ /2.3Y	20	64	210	-110	100	1×...2110/...2145
	60	0.95	220-275 ^Δ /380-480	4.2 ^Δ /2.3Y		70	255	-80	70	1×...2114/...2146
RHG 510-7H2	50	1.3	200-240 ^Δ /345-415	6.6 ^Δ /3.8Y	22	64	210	-170	170	1×...2110/...2145
	60	1.5	220-275 ^Δ /380-480	6.9 ^Δ /4.0Y		70	255	-150	140	1×...2114/...2146
RHG 510-7H3	50	1.6	200-240 ^Δ /345-415	7.5 ^Δ /4.3Y	23	64	210	-200	190	1×...2110/...2145
	60	2.05	220-275 ^Δ /380-480	7.6 ^Δ /4.4Y		70	260	-220	210	1×...2114/...2146
RHG 510-7H4	50	2.2	200-240 ^Δ /345-415	9.7 ^Δ /5.6Y	25	64	210	-220	270	1×...2110/...2145
	60	2.55	220-275 ^Δ /380-480	10.3 ^Δ /6.0Y		70	255	-260	290	1×...2114/...2146
RHG 520-7H1	50	3	200-240 ^Δ /345-415	12.5 ^Δ /7.2Y	40	72	230	-350	426	1×2B×2110/...2145
	60	3.45	220-275 ^Δ /380-480	12.6 ^Δ /7.3Y		74	275	-380	360	1×2B×2114/...2146
RHG 520-7H2	50	4	345-415 ^Δ /600-720	10.0 ^Δ /5.8Y	44	72	230	-390	490	1×2B×2110/...2145
	60	4.6	380-480 ^Δ /660-720	9.9 ^Δ /5.71Y		74	275	-410	480	1×2B×2114/...2146
RHG 530-7H1	50	0.85	200-240 ^Δ /345-415	4.0 ^Δ /2.3Y	21	65	270	-40	40	1×...2110/...2145
	60	0.95	220-275 ^Δ /380-480	4.2 ^Δ /2.4Y		71	330	-40	40	1×...2114/...2146
RHG 530-7H2	50	1.3	200-240 ^Δ /345-415	6.6 ^Δ /3.8Y	23	65	270	-100	100	1×...2110/...2145
	60	1.5	220-275 ^Δ /380-480	6.9 ^Δ /4.0Y		71	330	-90	80	1×...2114/...2146
RHG 530-7H3	50	1.6	200-240 ^Δ /345-415	7.5 ^Δ /4.3Y	24	65	270	-160	160	1×...2110/...2145
	60	2.05	220-275 ^Δ /380-480	7.6 ^Δ /4.4Y		71	330	-160	150	1×...2114/...2146
RHG 530-7H4	50	2.2	200-240 ^Δ /345-415	9.7 ^Δ /5.6Y	26	65	270	-220	230	1×...2110/...2145
	60	2.55	220-275 ^Δ /380-480	10.3 ^Δ /6.0Y		71	330	-230	210	1×...2110/...2146
RHG 590-7H1	50	1.1	200-240 ^Δ /345-415	5.7 ^Δ /3.3Y	23	64	215	-135	160	-
	60	1.7	220-275 ^Δ /380-480	6.0 ^Δ /3.5Y		71	255	-190	215	-