

RHG 1AC

HG系列

漩涡式气泵在真空和压力操作的选型和订购参数。单相电机

订单型号	马达				重量	噪音	最大流量	最大真空	最高压力	真空阀
	有库存	额定								
	HZ	输出功率 KW	电压 V	电流 A	KG	db(A)	m ³ /h	mbar	mbar	类型*型号
RHG 210-7A1	50	0.37	230	2	10	53	90	-110	110	1×2B×2110/...2141
	60	0.45	230	2.5		56	100	-140	140	1×2B×2114/...2142
RHG 230-7A1	50	0.37	230	2	10	54	110	-115	110	1×2B×2110/...2141
	60	0.45	230	2.5		57	140	-140	140	1×2B×2114/...2142
RHG 310-7A1	50	0.55	230	3.2	12	55	120	-120	120	1×2B×2114/...2142
	60	0.62	230	4		57	140	-135	150	1×2B×2114/...2142
RHG 310-7A2	50	0.7	230	4.3	12	55	120	-150	150	1×2B×2114/...2142
	60	0.8	230	3.9		57	140	-165	160	1×2B×2114/...2142
RHG 320-7A1	50	1.1	230	7	15	58	140	-240	280	1×2B×2110/...2141
	60	1.3	230	7.9		60	165	-230	260	1×2B×2114/...2142
RHG 330-7A1	50	0.7	230	4.3	12	56	165	-100	100	1×2B×2110/...2141
	60	0.8	230	3.7		58	175	-110	100	1×2B×2114/...2142
RHG 410-7A1	50	0.8	230	4.8	13	63	165	-150	160	1×2B×2110/...2141
	60	0.9	230	5.4		64	180	-160	140	1×2B×2114/...2142
RHG 410-7A2	50	1.1	230	7	14	63	165	-150	190	1×2B×2110/...2141
	60	1.3	230	7.8		64	180	-180	190	1×2B×2114/...2142
RHG 420-7A1	50	1.5	230	8.7	23	66	170	-280	290	1×2B×2110/...2141
	60	1.75	230	9.5		69	190	-250	280	1×2B×2114/...2142
RHG 430-7A1	50	0.8	230	4.7	14	64	190	-100	110	1×2B×2110/...2141
	60	0.9	230	5.5		66	220	-100	110	1×2B×2110/...2141
RHG 430-7A2	50	1.1	230	7	15	64	190	-170	210	1×2B×2110/...2141
	60	1.3	230	7.8		66	220	-145	145	1×2B×2114/...2142
RHG 510-7A1	50	1.1	230	7.1	20	64	220	-160	160	1×2B×2110/...2145
	60	1.3	230	8		70	276	-150	160	1×2B×2110/...2146
RHG 510-7A2	50	1.5	230	8.8	24	64	220	-190	200	1×2B×2110/...2145
	60	1.75	230	9.7		70	270	-180	180	1×2B×2110/...2146
RHG 530-7A1	50	1.5	230	8.5	23	65	290	-150	140	1×2B×2110/...2145
	60	1.75	230	9.8		71	355	-120	110	1×2B×2110/...2146
RHG 710-7A1	50	2.2	230	12.3	30	72	333	-190	190	1×2B×2110/...2141
	60	2.55	230	12.3		74	390	-190	200	1×2B×2114/...2146